

Features + equipment / Derinding machines

Maschinentyp	Andruckwalze			output conveyor	discharge r conveyor for	NOCK ICO®	NOCK ACTIVE SKIN	plastic modular	spring- suspended	tooth roller with	NOCK POWER	NOCK EASY-	lockable castors	stainless steel	particulary suitable for	
	gefedert	höhen- verstellbar	operation possible		removed skin	saftey system	GRIPPER® (ASG)	belts	blade holder mounting	scraper comb	PLATES®	FLOW® safety cover		3	small trade	industry
Cortex CB 435	•		•	0		0		0	•	•	•	•	•	•	•	•
Cortex CB 496	•	•	•	0	0	0		0	•	•	•	•	•	•	•	•
Cortex CB 503	•	•		•	0		0	0	•	•	•	•	•	•		•
Cortex CB 504	•	•		•	0		0	0	•	•	•	•	• 0	•		•
Cortex CB 604	•	•		•	0		0	0	•	•	•	•	• 0	•		•
Cortex CB 704	•	•		•	0		0	0	•	•	•	•	• 0	•		•
Cortex CB 501 SERRANO	•	•		•	0		0	0	•	•	•	•	•	•		•
Cortex C 420			•			0				•				•	•	
Cortex C 460 C 560			•			0			•	•	•		•	•	•	•
Cortex C 660 C 860			•			0			•	•	•		•	•		•
Cortex C 560 DBD			•			0			•	•	•		•	•		•

standard

optional

Further options:

- O Inflated pressure balloon (soft balloon)
- O NOCK Integrated Product Return System®
- O Pneumatic quick-adjustment of blade holder (CB 501)
- O Transfer plate for passing without derinding

- alternative: without underframe for integration in cutting lines
- 2 requires compressed air
- 3 including of all rolling bearings

Subject to technical changes Issued: 10/2016