

## Technical data / Fish skinning machines

machine model	cutting width	cutting performance	blade gap (stepless)	maximum throughput height	apply length on infeed belt	overall measurements W x H x D	weight	motor performance	electrical connection	water connection	approx. water connection
Freeze Drum Skinner TFE 350A	370	8 - 20	0 - 10	40	450	1550 x 1500 x 2600	680	5.0	3 AC - 400 V - 50 Hz ①	l/h	150
Freeze Drum Skinner TFE 350W	370	8 - 20	0 - 10	40	450	1550 x 1500 x 2600	660	5.0		G 3/4" external thread	150 +600 ④
Freeze Drum Skinner TFE 550W	570	8 - 20	0 - 10	40	450	1750 x 1500 x 2600	820	7.5			150 +1000 ④
Cortex CBF 496	430	24	0 - 5	70	400	800 x 1190 x 1860	240	0.75		G 1/4" internal thread	200
Skinex SB 496	430	24	0 - 5	70	400	800 x 1190 x 1860	240	0.75			200
Skinex QS 888	2 x 200	29 ②	0 - 0.5	40	540	800 x 1190 x 1820	240	1.1		G 1/2" internal thread	200
Cortex CF 460	430	19	0 - 0.5	-	-	750 x 960 x 750	150	0.75			100
Skinex S 460	430	29	0 - 0.5	-	-	750 x 960 x 750	160 ③	0.75			100
Cortex CF 420	430	19	0 - 0.5	-	-	700 x 420 x 500 (700 x 950 x 600) ③	80 (95) ③	0.75		G 1/4" internal thread	80
Skinex S 420	430	24	0 - 0.5	-	-	700 x 420 x 500 (700 x 950 x 600) ③	80 (95) ③	0.75			80
Cortex CF 300 COUNTERBOY	280	19	0 - 0.5	-	-	560 x 320 x 400 (560 x 950 x 500) ③	50 (65)	0.25			50

- ① other voltages available upon request
- ② speed of infeed conveyor belt
- ③ with underframe
- ④ cooling water (tap water)



**NOCK Maschinenbau GmbH**  
 Industriestrasse 14  
 77948 Friesenheim  
 GERMANY

Tel: +49 (0) 7821-92 38 98-0  
 Fax: +49 (0) 7821-92 38 98-18  
 E-mail: info@nock-gmbh.com  
 www.nock-gmbh.com