

## Technical data + equipment / Doner and Gyros cutting machines

	Cortex CB 503 KEBAB	Cortex CB 703 KEBAB	Cortex CB 496 GYROS
cutting width (mm)	500	700	430
cutting speed (m/min)	28	28	24
NOCK Integrated Product Return System®	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
alternative: output conveyor for remaining uncut piece	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
output conveyor for sliced meat	<input type="checkbox"/>	<input type="checkbox"/> <sup>4</sup>	<input type="checkbox"/>
plastic modular belts	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
pressure roller spring suspended adjustable in height	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
blade gap infinitely adjustable (mm)	0.5 – 8 <sup>1</sup>	0.5 – 8 <sup>1</sup>	0.5 – 8 <sup>1</sup>
apply length on infeed conveyor (mm)	400 <sup>3</sup>	400 <sup>3</sup>	400 <sup>3</sup>
tooth roller with scraper comb	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
blade holder spring suspended	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
max. throughput height (mm)	90	90	90
lockable steering castors	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
NOCK POWER PLATES®	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
motor performance (kW)	1.1	1.1	0.75
electrical connection	3 AC - 400 V – 50 Hz <sup>2</sup>		
weight (kg)	235 <sup>3</sup>	300 <sup>3</sup>	210 <sup>3</sup>
overall dimension W x H x D (mm)	980 x 1190 x 1360 <sup>3</sup>	1065 x 1190 x 1360 <sup>3</sup>	910 x 1190 x 1210 <sup>3</sup>
stainless steel	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
stainless steel ball bearings	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
available as a multi-cut line	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

<sup>1</sup> optional: other thickness ranges

<sup>2</sup> other voltages upon request

<sup>3</sup> with NOCK Integrated Product Return System®, without output conveyor for sliced meat

<sup>4</sup> not necessary because a standard trolley (USDA/DIN 9797) can be placed below the machine

**standard**

**optional**

NOCK Maschinenbau GmbH  
Industriestrasse 14  
77948 Friesenheim  
GERMANY

Tel: +49 (0) 7821-92 38 98-0  
Fax: +49 (0) 7821-92 38 98-18  
E-mail: info@nock-gmbh.com  
www.nock-gmbh.com