



*Know-how in food processing!*



## **Poultry skinning machine Cortex CBP 496 VARIO**

**Economical skinning of chicken corpus**

# Poultry skinning machine



Know-how in food processing!

## Cortex CBP 496 VARIO

### Features and application range

- Conveyorized double lane skinning machine for chicken corpus (chicken breast with skin and bone)
- cutting speed: 24 m/min
- cutting width: 2 x 160 mm

### Standard equipment

- Special pressure roller (paddle roller) with variable speed and adjustable counterweight for chicken corpus
- infeed conveyor
- discharge conveyor
- special poultry skinning blade
- blade holder spring suspended
- special transport roller for poultry skinning
- dynamic (counter-rotating) stainless steel cleaning roller
- NOCK Air-Jet compressed air cleaning system
- NOCK POWER PLATES® for special robustness and service-friendliness
- NOCK EASY-FLOW® Safety cover for reliable product flow and better processing hygiene
- lockable castors
- stainless steel
- stainless steel bearings

### Options:

- discharge conveyor for removed skins
- plastic modular belts
- sister models CBP 496 POULTRY and CBP 695 POULTRY for skinning of chicken breast without bone, whole chicken legs, thighs and drumsticks



## Technical data / Cortex CBP 496 VARIO

cutting width	2 x 160 mm	motor performance	0.75 kW
cutting speed	24 m/min	electrical connections	3 AC - 400 V - 50 Hz IEC 60309 16 A 6h other voltages upon request
maximum throughput height	160 mm	compressed air connection	5 < p < 10 bar plug coupling DN 7.2 (G1/4 external)
apply length on infeed conveyor	530 mm		
infeed conveyor <sup>①</sup>	1370 x 425 mm	compressed air consumption	approx. 250 l/min (surrounding pressure)
output conveyor <sup>①</sup>	850 x 425 mm		
discharge conveyor for removed skin <sup>①</sup>	650 x 425 mm	water consumption	not required
overall dimension W x H x D	800 x 1250 x 2380 mm		
weight	265 kg		

① external dimensions of the conveyor frame



**NOCK Maschinenbau GmbH**  
Industriestrasse 14  
77948 Friesenheim  
GERMANY

Tel: +49 (0) 7821-92 38 98-0  
Fax: +49 (0) 7821-92 38 98-18  
E-mail: [info@nock-gmbh.com](mailto:info@nock-gmbh.com)  
[www.nock-gmbh.com](http://www.nock-gmbh.com)